



NVR5XX-4KS2_V3.216.0000002.0.R.181106


Release Note




Perimeter Protection




Metadata



Thermal camera



Multi-Sensor Camera
(No splice)



3D People
Counting Camera

Applicable products	GDP NO.	Version
NVR5XX-4KS2 series	2.6.01.02.01465	General_NVR5XXX-4KS2_MultiLang_V3.216.0000002.0.R.20181106
	2.6.01.02.01462	DH_NVR5XXX-4KS2_MultiLang_V3.216.0000002.0.R.20181106
	2.6.01.02.01464	General_NVR5XXX-4KS2_EngMSP_V3.216.0000002.0.R.20181106



High Compatibility



Perimeter Protection
by Camera

- ✓ Up to 16 channel perimeter protection AI cameras input
- ✓ Setting tripwire or intrusion trigger actions caused by human or vehicle
- ✓ Support AI search by channel, time and object(human or vehicle)
- ✓ Export video and pictures via USB



Metadata by Camera

- ✓ Support metadata AI cameras input
- ✓ Support AI search by channel, time and metadata
- ✓ Export video and pictures via USB



Thermal camera

- ✓ Support thermal camera input
- ✓ Configure trigger actions when fire or temperature alarm occurs
- ✓ Real-time temperature testing when previewing



Multi-Sensor Camera
(No splice)

- ✓ Support the new released multi-sensor camera input
- ✓ Manually add: Enter the IP and the correct username and password, and then click Connect. All the channels of the device will be displayed
- ✓ PoE add: the first channel of the device will be connected to the POE port, and other channels to non-POE idle channels of NVR.



3D People
Counting Camera

- ✓ Support 3D people counting camera input
- ✓ Support export daily, monthly or yearly report from NVR local or websites